Reference data
Ellipse ASR 375 UNI
MGE UPS SYSTEMS

Product	MGE Ref	Short description
Ellipse ASR 375 UNI	66763	Professional UPS, compact protection for PC and Mac, 375VA/225W, ASR technology, slim-line design, versatile form factor, Phone/Fax/Modem/Internet + Ethernet 10/100 protection, 4 outlets (2 IEC + 1 UNIverselle with battery back up and lightning protection + 1 UNIverselle with lightning protection only dedicated to peripherals), warranty of connected computer equipment for an unlimited amount

Packaging	Size (H x W x D*mm)	Weight (kg)	Number of Units / Packaging	Bar Code
Individual packaging	142 x 332 x 366	5,8 kg	1 product / carton	3553340667633
Complete pallet	1142 x 1000 x 1200	365,4 kg	63 cartons / pallet	

Package content (Retail color packaging)
UPS with 4 outlets without input cable (use pc's cable) + 2 IEC output cables + 17-language User manual + warranty of connected computer equipment

Technical specifications	
Technology	UPS Off-line High Frequency with ASR technology (Advanced Surge Reduction)
Power output	375 VA / 225 W
Size (H x W x D*)	270 x 82 x 265 mm
Outlets	4,2 kg
Outlets	4 outlets (2 IEC + 1 UNIverselle with battery back up and lightning protection + 1 UNIverselle with lightning protection only)
Output voltage	230 V
Frequency	50 / 60 Hz autoselect
Input voltage	161V-284V adjustable with push button
Max output current	Total 10 A max (1,63 A max on outlets with battery backup + lightning protection)
Features	Automatic battery test, battery replacement indicators, lightning protection visual indicator, resettable circuit breaker, audible alarm (can be deactivated), permanent battery recharge (even when off)
Lightning protection	3 MOV - Total energy dissipation : 525 Joules Compatible with IEC 61643-1 standards for lightning protection Performances tested according to IEC 61 643-1 standard for Surge Protective Device on an 8/20 µs waveform : Uoc = 5 kV, Up = 1,7 kV, In = 2,5 kA, I max = 8 kA
Data line protection	Phone/Fax/Modem/Internet ADSL + Ethernet 10/100 protection
Warranty	2 years ; optional Warranty + contract for 3-year warranty (country specific) warranty of connected computer equipment for an unlimited amount, applicable in EU countries and Norway only, reserved to natural persons (individuals) and liberal professions
Technical standards	IEC 60 950-1, IEC 62040-1-1, EN50 091/CFR part 15, IEC 61 643-1, CE mark

Typical use	Operating systems compatibility	Runtime
1 PC with CRT 15'' monitor	- Windows XP/2003/2000/98/95/Me/NT - Mandrake Linux / Mandriva Linux - Red Hat Linux - SUSE Novell - Debian GNU/Linux	30 min
1 PC with CRT 17'' monitor		25 min
1 Apple eMac with 17'' monitor	Mac OS X	25 min

Key selling points
✓ Ideal protection 375VA/225W for PC and Mac
✓ Compact slim-line design : saves desk space, versatile installation : vertical or horizontal
✓ ASR Technology compatible with IEC 61643-1 standards for lightning protection
✓ Easy connecting with 4 outlets (2 IEC + 1 UNIverselle with battery back up and lightning protection + 1 UNIverselle with lightning protection only)
✓ Phone/Fax/Modem/Internet ADSL + Ethernet 10/100 protection
✓ Replaceable battery
✓ Warranty of connected computer equipment for an unlimited amount
✓ Audible alarm (can be deactivated)
✓ Lightning protection visual indicator : on mains, on battery, status of battery, overload, status of lightning protection
✓ Resettable circuit breaker
✓ Optional kit : 19'' rack installation kit

* H x W x D = Height x Width x Depth

MGE UPS SYSTEMS